

DUCHATEAU

SIGNATURE

GRANDE SAVOY

SIEGNEUR




PRODUCT ID	GRSSGN8-1	SPECIES	EUROPEAN OAK	SHEEN	MATTE
WEAR LAYER	4 MM ¹	CONSTRUCTION	ENGINEERED	INSTALLATION	GLUE-DOWN OR NAIL/STAPLE
AVAILABLE WIDTH	9-1/2 INCHES (240 MM)	GRADE	CHARACTER	RADIANT HEAT	APPROVED (SEE INSTALLATION INSTRUCTIONS)
LENGTH	RANDOM LENGTH UP TO 86-11/16 INCHES (2200 MM)	FINISH	UV OIL	WARRANTY	LIMITED LIFETIME STRUCTURAL INTEGRITY 25-YEAR RESIDENTIAL SURFACE FINISH 3-YEAR COMMERCIAL SURFACE FINISH
COVERAGE PER BOX	34.1 SQ.FT	SURFACE TREATMENT	SMOOTH WITH ULTRA MATT FINISH	TRIM	STAIRNOSE, REDUCER, THRESHOLD, T-MOLD, AND SQUARENOSE
WEIGHT PER BOX	71 POUNDS	THICKNESS	5/8 INCH (15 MM)		

RELATIVE HUMIDITY (in %)



VARIATION GUIDE



This bar shows examples of the natural variation and graining you should expect with this flooring.

DUCHATEAU.COM | 1.888.DUCHATEAU

Product Sample Disclaimer: Created to be a truly individual piece of nature's artistry, each and every DUCHATEAU product carries distinct variations in size, shape, thickness, finish, texture, grain and overall character. This is how we develop the unique diversity and natural elegance of our flooring. Individual samples of these floors are merely for reference and not meant to serve as exact representations; it is virtually impossible to capture—in a single image or physical sample—the entire range of color variation and character that will be present in the flooring you will receive. To better understand the unique look of DUCHATEAU finished floor in your space, we recommend consulting your sales representative for more details.

Installation and Performance Disclaimer: Environmental conditions, such as exposure to light, and fluctuations in temperature and humidity, can affect product performance from initial installation throughout its life. Refer to our website for installation guidelines or see your local sales representative for more information on proper steps and specific environmental conditions to successfully install, care for and ensure the lifelong performance of your floor.

Note: All measurements are nominal.
¹ Nominal wear layer thickness measured prior to finishing processes. Finishing processes such as wire-brushing will affect the overall thickness.
² Starter boards included in each box
2100, 171 FSC® Title V Compliant.

©DUCHATEAU | All rights reserved.



GRSSGN8-SB